



TRIP1

The tripods are anchorage devices designed to enable anchor points during work at confined spaces. This type of work requires the use of one anchor point (at least) which enables to work with efficiency and total safety. Tripods are made of aluminium, which enables to transport them easily.

CHARACTERISTICS:

- Aluminium alloy head: to add robustness and durability to the system.
- Embedded pulley: for a more rigid functioning of the winch (Trip 1).
- 2 aluminium anchorage rings: to connect up to two systems (at least one fall arrest system).
- Aluminium legs: a higher lightness.
- Adjustable to 9 different heights.
- Robust: capacity up to 500kg loads.
- Non-slip rubbers: for an optimal stability.
- Safety strap: Prevents unintentional leg movement.
- Certified for work at explosive environments ATEX II 2G Ex h II c T6.
- Equipped with transport bag.

| | |
|-------------------------|------------------------------------|
| Norm | EN795 B ATEX II 2G Ex h II c T6 |
| Weight | 12,1 Kg |
| Access max. Diameter | 1,2-1,8m |
| Height | 1,40-2,15m |
| Max. Load | 500 Kg |
| Anchorage rings | 2 |
| Pulleys on head | 1 |
| Height positions | 7 |
| Lifetime | Unlimited |

| Material | |
|----------------|------------|
| Head | Aluminium |
| Legs | Aluminium |
| Rings | Aluminium |
| Anti-slip foot | Rubber PVC |
| Security tape | Polyester |